



Depump Technology Shijiazhuang Co., Ltd.

Pump List

Part 1: The Complete Series Of Depon Slurry Pumps

Conatct: Norky Wei Phone: 86 18330173287 Email: norky@deponpump.cn
whatsapp:18830289136

Depon MAH(R) slurry pump



Usage: Slurry, Sewage and water

Technical Data:

Capacity: Up to 3600m³/hr (1000 l/s)

Head: Up to 112m (367 feet)

Speed: Up to 3200 rpm

Size : NB 25 to NB 350 (1' up to 14')

Temperature: Max. 110°C

Drive: Diesel or Electric

Depon MHH(R) high head slurry pump



Usage: Slurry, Sewage and water

Technical Data:

Capacity: Up to 1260 m³/hr (350 l/s)

Head: Up to 200 m (656 feet)

Speed: Up to 1800 rpm

Size : NB 150 to NB 250 (6' up to 10')

Temperature: Max. 110°C

Drive: Diesel or Electric

Depon MSP(R) vertical slurry pump



Usage: Slurry, Sewage and water

Technical Data:

Capacity: Up to 1267m³/hr (352 l/s)

Head: Up to 43 m (141 feet)

Speed: Up to 1500 rpm

Size : NB 40 to NB 250 (1.5' up to 10')

Temperature: Max. 110°C

Drive: Diesel or Electric

Depon MZJ slurry pump



Usage: Slurry, Sewage and water

Technical Data:

Capacity: Up to 2500m³/hr (694 l/s)

Head: Up to 130m (426 feet)

Speed: Up to 3200 rpm

Size : NB 40 to NB 350 (1.5' up to 14')

Temperature: Max. 110°C

Drive: Diesel or Electric

Depon MZGB sand pump



Usage: Slurry, Sewage and water

Technical Data:

Capacity: Up to 1800 m³/hr (500 l/s)

Head: Up to 94 m (308 feet)

Speed: Up to 1480 rpm

Size : NB 65 to NB 300 (2.5' up to 12')

Temperature: Max. 110°C

Drive: Diesel or Electric

Depon SS Submersible slurry pump



Usage: Slurry, Sewage and water

Technical Data:

Capacity: Up to 2400 m³/hr (666 l/s)

Head: Up to 60m (196 feet)

Speed: Up to 1480 rpm

Size : NB 80 to NB 400 (3.15' up to 16')

Temperature: Max. 110°C

Drive: Diesel or Electric

Slurry Pump Series Features

Handled liquids : Mining Dewatering, Ore slurry, Ash, Iron, Bauxite, Bronze, Sand...

Applications : Power plant, Coal washing, Mining, Cement, Steel plants...

Advantages	Material Option	Nihard, Hi-chrome alloy, 27%
		Martensitic white iron, Ni-hard 1
		Chromium/ Molybdenum, Cr15Mo3
		28%Cr, Low Carbon, A49
	Bearings	Heavy duty bearings and Original FAG Bearings
	Shaft & Sleeve	SS304, SS316, 40Cr, #40 Steel optional
	Sealing	Stainless Steel Single or double mechanical seals
Hi-seal		
PTFE Packing		

Part 2: The Complete Series Of Depon Water Pumps

Conatct: Norky Wei Phone: 86 18330173287 Email: norky@deponpump.cn
whatsapp:18830289136

Depon MIS water pump



Usage: Clean water

Technical Data:

Capacity: Up to 1900m³/hr (527 l/s)

Head: Up to 125 m (410 feet)

Speed: Up to 2900 rpm

Size : NB 50 to NB 350 (2' up to 10.5')

Temperature: Max. 150°C

Drive: Diesel or Electric

Milestone MS double suction water pump



Usage: Clean water

Technical Data:

Capacity: Up to 30000m³/hr (8333 l/s)

Head: Up to 230m (755 feet)

Speed: Up to 2960 rpm

Size : NB 150 to NB 1600 (6' up to 64')

Temperature: Max. 120°C

Drive: Diesel or Electric

Milestone MDA multistage water pump



Usage: Clean water

Technical Data:

Capacity: Up to 840m³/hr (233 l/s)

Head: Up to 680m (755 feet)

Speed: Up to 2950 rpm

Size : NB NB 50 to NB 200 (2' up to 8')

Temperature: Max. 150°C

Drive: Diesel or Electric

Depon deep well QJ submersible multistage water pump



Usage: Clean water

Technical Data:

Capacity: Up to 2200m³/h

Head: Up to 3000m³/h

Speed: Up to 2900 rpm

Power: Up to 710kw

Max well Dia. 900mm

Drive: Electric

Water Pump Series Features

Handled liquids : Clear water, Municipal water supply, fire protection, water transfer

Applications : Power plant, Coal washing, Mining, Cement, Steel plants...

Advantages	Material Option	Cast iron, duct alloy, carbon steel, zinc free bronze,
		silicon brass or stainless steel construction,
		Other materials available on request.
	Bearings	Heavy duty bearings and Original FAG Bearings
	Shaft & Sleeve	SS304, SS316, 40Cr, #40 Steel optional
	Sealing	Stainless Steel Single or double mechanical seals
Hi-seal		
PTFE Packing		

Part 3: The Complete Series Of Depon Sewage Pumps

**Conatct: Norky Wei Phone: 86 18330173287 Email: norky@deponpump.cn
whatsapp:18830289136**

Depon MWQ submersible sewage pump



Usage: Sewage & Clean water

Technical Data:

Capacity: Up to 5760m³/hr (1600 l/s)

Head: Up to 62m (203 feet)

Speed: Up to 2880 rpm

Size : NB NB 50 to NB 600 (2' up to 23')

Temperature: Max. 155°C

Drive: Electric

Depon MZW/ZX Self-priming pump



Usage: Sewage & Clean water

Technical Data:

Capacity: Up to 800m³/hr (222 l/s)

Head: Up to 80m (262 feet)

Speed: Up to 2900 rpm

Size : NB NB 25 to NB 300 (1' up to 12')

Temperature: Max. 200°C

Drive: Diesel or Electric

Sewage Pump Series Features

Handled liquids : Clear water, Municipal water supply, fire protection, water transfer

Applications : Water Treatment, Building Services, Sumps and Basements, Mining, Civil, Construction, Industry, Municipal, Processing

Advantages	Material Option	Cast iron, duct alloy, carbon steel, zinc free bronze,
		silicon brass or stainless steel construction,
		Other materials available on request.
	Bearings	Heavy duty bearings and Original FAG Bearings
	Shaft & Sleeve	SS304, SS316, SS420, 40Cr, #40 Steel optional
	Sealing	Stainless Steel Single or double mechanical seals
Hi-seal		
PTFE Packing		

Part 4: The Complete Series Of Depon Chemical Pumps

**Conatct: Norky Wei Phone: 86 18330173287 Email: norky@deponpump.cn
whatsapp:18830289136**

Depon MIH chemical pump



Usage: Chemical water, corrosive liquid

Technical Data:

Capacity: Up to 1900m³/hr (527 l/s)

Head: Up to 125 m (410 feet)

Speed: Up to 2900 rpm

Size : NB 50 to NB 350 (2' up to 10.5')

Temperature: Max. 105°C

Drive: Diesel or Electric

Depon MAFB chemical pump



Usage: Chemical water, corrosive liquid

Technical Data:

Capacity: Up to 200m³/hr (55 l/s)

Head: Up to 64 m (209 feet)

Speed: Up to 2900 rpm

Size : NB 25 to NB 150 (0.75' up to 4.5')

Temperature: Max. 130°C

Drive: Diesel or Electric

Depon MAFB vertical chemical pump



Usage: Chemical water,corrosive liquid

Technical Data:

Capacity: Up to 1235m³/hr (343 l/s)

Head: Up to 28 m (92 feet)

Speed: Up to 2900 rpm

Size : NB 20 to NB 80 (0.8' up to 3.2')

Temperature: Max. 130°C

Drive: Electric

Chemical Pump Series Features

Handled liquids : Chemical water,corrosive liquid

Applications : Food, Medicine, Petroleum, Metallurgy, synthetic fiber, Chemical

Advantages	Material Option	SS303, SS304, SS316
		RPP, PVDF,ABS.
		Other materials available on request.
	Bearings	Original FAG Bearings
	Shaft & Sleeve	SS304, SS316, 40Cr, #40 Steel optional
Sealing	Stainless Steel Single or double mechanical seals	